

POWERMAKER 6DV5



SPECIFICATION	
AUXILIARY OUTPUT - SINGLE PHASE	120/240V 5.5kW 50Hz
AUXILIARY SOCKETS	240V - 1 x 16A & 1 x 32A 120V - 1 x 16A & 1 x 32A
AVERAGE SOUND PRESSURE LEVEL @ 7m	62dB(A)
ENGINE	Kubota Z482 2 cylinder, water-cooled 3000rpm Stage V
FUEL TANK CAPACITY (L)	25
FUEL CONSUMPTION (L/hr) @75% LOAD	2
RUNNING TYPE (hrs)	12.5
DIMENSIONS LxWxH (mm) SKID MOUNTED ON WHEELBARROW ON ROAD TRAILER	1170 x 670 x 805 1220 x 880 x 1080 2280 x 1270 x 1210
WET WEIGHT (kg) SKID WHEELBARROW ROAD TRAILER	265 300 335

Safety Features

Auto engine shutdown will operate in the event of low oil pressure, high water temperature, thermal overload, insufficient speed or with door opening for enhanced safety.

RCBO fitted for increased site safety.

Stage V Engine

This model complies with the European Regulation 2016/1628 NRMM on StageV gas emissions.



Applications

The information included in this document is only illustrative, it may vary without prior notice and therefore no contractual relationship is established. The logos, trademarks and data may be subject to copyright of their respective companies.

Features

Super silent operation reduces noise pollution.

Water cooled Kubota engine for enhanced reliability & longevity.

Dual-voltage output available simultaneously.

Compact & lightweight available trolley mounted or on fast tow road trailer.

Standby duty rating of 6.1kW continuous duty rate of 5.5kW at a power factor of 1.0.

Brushless generator reduces maintenance costs.

Hard wire facility for use with distribution boards.

Offshore Specification:

- Spark arrestor
- Chalwyn valve
- Drip tray
- Fuel water trap
- Anti-static fan belt
- Braided fuel lines
- Battery isolator switch
- Fuel isolator shut off valve

Optional Specifications:

Petrolchemical Specification:

- Spark arrestor
- Chalwyn valve

