HILTA

"2" PETROL DIAPHRAGM PUMP

Features

- High solids handling.
- Petrol.
- 'Snore' allows machine to run dry with no damage to the pump end.
- Easy wheel chassis.

Specifications

MØRRIS MACHINERY



	· · · · · · · · · · · · · · · · · · ·
SIZE	2"
MODEL	Sprite
HILTA REF	H000155
FRAME/CHASSIS TYPE	Easy Wheel
POWER SOURCE	Petrol - Honda GX120 2850rpm Stage V
AVERAGE SOUND PRESSURE LEVEL @ 7m	79dB(A)
MAXIMUM OUTPUT	11.36m/hr (2500gal/hr)
MAXIMUM DRY SUCTION LIFT	6 Metres
MAXIMUM DELIVERY HEAD	12 Metres
MAXIMUM SOLIDS	20mm
STARTING	Recoil
FUEL TANK CAPACITY (LITRES)	2.5 L
DIMENSIONS (LxWxH)	740 x 450 x 570mm
WET WEIGHT	45kg

Stage V Engine

This model complies with the European Regulation 2016/1628 NRMM on StageV gas emissions.



Applications

All hoses and fittings available for all pumps. The information included in this document is only illustrative, it may vary without prior notice and therefore no contractual relationship is established. The logos, trademarks and data may be subject to copyright of their respectives companies.



