
TITALTOWER® ASTRID HYBRID



MRRIS



Technical Specification	
Rated Frequency	50 Hz
Rated Power	3.5 Kw
Operating Temperature	-40/+50°C
Sound Level	61 db
Control Unit	DeepSea 7320

Generator	
Model	Yanmar 2TNV70
Speed	1500 rpm
Coolant	Liquid
Cylinders	2
Emissions	Stage V
Altenator	Linz Alumen

Battery Pack	
Туре	Crystal
Batteries number	4
Battery pack	24VDC 200 Ah

Galvanizing Mast		Energy Consumption	
Height	8.5m	Fuel Consumption (charging)	1
Lifting system	Hydraulic	Re-charging time (LED off)	3 h
Rotation	350°	Running time from battery	11.30
Speed Resistance	110 km/h	Tank	12
		Fuel	Die
anopy d Trailer		Running Time hybrid mode 4x120W Led	<48

Shipment	
Dimension	L2380 x W1480 x H2400mm
Weight	1000kg
Deployed dimensions	L2380 x W1820 x H8500mm

Galvanizing Mast	
Height	8.5m
Lifting system	Hydraulic
Rotation	350°
Wind Speed Resistance	110 km/h

Canopy and Trailer	
Trailer	Road tow trailer - EU type approved
AMOSS	Included
Tyres	185/80R13
Stabilizers	4+1 (Wheel)
Canopy	Powder coated paint

Picture for illustration purpose only. Specifications are subject to change without prior notice.



