

GENPAC 10

MORRIS
MACHINERY



STAGE V
EMISSIONS COMPLIANT

SPECIFICATION	
AUXILIARY OUTPUT - SINGLE PHASE	10KVA 240/110V
AUXILIARY SOCKETS	1 x 32A 240V 2 x 16A 1 x 32A 110V 2 x 16A 240V
AVERAGE SOUND PRESSURE LEVEL @ 7m	65dB
ENGINE	KUBOTA D1105 Stage V
FUEL TANK CAPACITY (L)	40 Litres
FUEL CONSUMPTION (L/hr) @75% LOAD	2 Litres Per Hour
RUNNING TYPE (hrs)	20 Hrs
DIMENSIONS LxWxH (mm)	1360 X 675 X 860 MM
WET WEIGHT (kg)	457 KG

Safety Features

Auto engine shutdown will operate in the event of low oil pressure, high water temperature, thermal overload, insufficient speed or with door opening for enhanced safety.

RCBO fitted for increased site safety.

Stage V Engine

This model complies with the European Regulation 2016/1628 NRMM on StageV gas emissions.

Features

Super silent operation reduces noise pollution.

Water cooled Kubota engine or enhanced reliability & longevity.

Dual-voltage output available simultaneously.

Compact & lightweight available trolley mounted or on fast tow road trailer.

Standby duty rating of 8kW continuous duty rate of 5.5kW at a power factor of 1.0.

Brushless generator reduces maintenance costs.

Hard wire facility for use with distribution boards.

Optional Specifications: Petrolchemical Specification:

•



Applications

The information included in this document is only illustrative, it may vary without prior notice and therefore no contractual relationship is established. The logos, trademarks and data may be subject to copyright of their respective companies.

